

This R.T.V. Sealant Adhesive can be used on metal, glass, porcelain, ceramics, wood, rubber, and most paint and plastics. As an instant gasket maker, this product replaces a wide range of cork, paper, asbestos, felt and metal gaskets. This product has excellent adhesion characteristics, high chemical resistance and will not sag or shrink. Withstands intermittent temperatures up to 650°F and pressures up to 350 psi. Offers unmatched performance under the most severe operating conditions. Virtually unaffected by chemical deterioration, extreme weather, temperature or aging.

FORMS IN-PLACE GASKETS and SEALS FOR:

Pumps, High Pressure Pipe Joints, Oil and Transmission Pans, Oil and Water Pumps, Valve and Timing Chain Covers, Electric Motors and Electrical Control Boxes, Gear Boxes, Compressors, Machine Covers, Rigid Flange Assemblies, Equipment Housings.

DIRECTIONS:

Read Material Safety Data Sheet before using.

1. Surface must be clean, dry and free of oil, tar, dirt and dust for best adhesion.
2. Hold can at 45° angle and apply a continuous bead of 1/16" to 1/8" to the mating surface, encircling all bolt holes.
3. For adhesion to both parts, assemble immediately. One part adhesion, allow 10-15 minutes for bead to skin.
4. Assemble parts, but do not squeeze gasket out by over tightening bolts.
5. Starts to cure immediately, fully cures in 24 hours and reaches optimum strength in 7 days.
6. After sealant is completely cured, for food applications, wash part before use. Excess cured material can be removed by trimming with a sharp blade. Avoid undercutting the seal.

NOT RECOMMENDED FOR USE ON: Cylinder heads, exhaust manifolds, intake manifolds, carburetors, or parts requiring continuous immersion in gasoline.

CAUTION: CONTACT WITH UNCURED SEALANT CAUSES IRRITATION. OUTER CONTAINER IS PRESSURIZED WITH A FLAMMABLE HYDROFLUOROCARBON PROPELLANT. DO NOT REMOVE RUBBER PLUG IN BOTTOM OF CONTAINER.

Use with adequate ventilation. Product releases acetic acid (vinegar-like odor) during curing. Contact lens wearers take appropriate precautions. Contents under pressure. Do not puncture or incinerate. Do not store at temperatures above 120°F (50°C). Do not store in automobiles, in direct sunlight or any area with temperatures above 120°F.

CONTAINS: Amorphous Silica (7631-86-9), Methyltriacetoxysilane (4253-34-3), Ethyltriacetoxysilane (17689-77-9) and Difluoroethane (75-37-6).



MADE IN THE U.S.A.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Seek medical attention immediately. IF SKIN CONTACT: Wipe off excess sealant with dry paper towel or cloth, and wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. IF **INGESTED:** Do not induce vomiting. No additional first aid should be needed.

TERAND
INDUSTRIES, INC.

P.O. Box 667770 • Pompano Beach, FL 33066
www.terandstore.com


TERAND
The Maintenance Professional's Choice

**RTV
SILICONE
GASKET MAKER**
RED (HIGH TEMPERATURE)
11507

After each use, leave a small bead of material, which will form a sealing plug for reuse. To use, gently pull plug and begin to use material. If plug breaks, leaving the dispensing lip sealed, use a paper clip or other wire object to remove and loosen the remainder of the cured material.



1	1	0	B
HEALTH	FLAMMABILITY	REACTIVITY	PERSONAL PROTECTION
HMIS RATING			



Seals, Bonds, Insulates
Low Volatile • Flexible • Easy to Use
Economical • Eliminates Waste
Waterproof • Weatherproof
Eliminates: Squeeze Tubes and Cartridge Guns
100% Low Volatile R.T.V. Silicone
Meets G.M. and O.E.M. specifications
Safe to use on oxygen sensor equipped vehicles
Pressurized dispenser makes any size or shape gasket instantly
Remains permanently flexible at temperatures from -60°F to +600°F
Eliminates need to stock conventional gaskets and seals
Reduces down time - gets equipment back in operation fast

CAUTION: CONTACT WITH UNCURED SEALANT CAUSES IRRITATION. CONTENTS UNDER PRESSURE OUTER CONTAINER IS PRESSURIZED WITH A FLAMMABLE HYDROFLUOROCARBON PROPELLANT. DO NOT REMOVE RUBBER PLUG IN BOTTOM OF CONTAINER. SEE OTHER CAUTIONS ON BACK PANEL. KEEP OUT OF REACH OF CHILDREN.
NET WT. 8 OZ. (227 Grams)