

This R.T.V. Silicone Caulk and Sealant is ideal for use wherever a strong permanently elastic weatherproof caulk, sealant or adhesive is needed. Designed to seal non-porous surfaces around ceramic tile, cultured marble, showers, tubs, sinks and plumbing fixtures. Ideal for caulking windows, doors, sills and ceiling cracks and crevices.

Features excellent adhesion and high chemical resistance. Will not sag or shrink during severe temperature changes. Useful for sealing cracks in machinery, heating and ventilation duct work, plumbing fixtures, electrical connections and low pressure water and drain lines.

Bonds nameplates, machinery flanges, glass, signs, electrical insulation etc. Offers unmatched performance under the most severe conditions. Remains flexible and will not shrink, crack, crumble or dry out.

NOTE: Paint will not adhere to cured material. Not recommended for continuous immersion in water or application to porous surfaces such as masonry.

DIRECTIONS:

Read Material Safety Data Sheet before using.

1. Surface must be clean, dry and free of oil, tar, dirt and dust for best adhesion.
2. Hold can at 45° angle and apply a continuous bead of 1/16" to 1/8" to the mating surfaces.
3. Starts to cure immediately, fully cures in 24 hours and reaches optimum strength in 7 days.

CAUTION: CONTACT WITH UNCURED SEALANT CAUSES IRRITATION. OUTER CONTAINER IS PRESSURIZED



MADE IN THE U.S.A.

WITH A FLAMMABLE HYDROFLUOROCARBON PROPELLANT. DO NOT REMOVE RUBBER PLUG IN BOTTOM OF CONTAINER.

Use with adequate ventilation. Product releases acetic acid (vinegar-like odor) during curing. Contact lens wearers take appropriate precautions. Contents under pressure. Do not puncture or incinerate. Do not store at temperatures above 120°F (50°C). Do not store in automobiles, in direct sunlight or any area with temperatures above 120°F.

CONTAINS: Amorphous Silica (7631-86-9), Methyltriacetoxysilane (4253-34-3), Ethyltriacetoxysilane (17689-77-9) and Difluoroethane (75-37-6).

FIRST AID: IF EYE

CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Seek medical attention immediately. **IF SKIN**

CONTACT: Wipe off excess sealant with dry paper towel or cloth, and wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF**

INGESTED: Do not induce vomiting. No additional first aid should be needed.

After each use, leave a small bead of material, which will form a sealing "plug" for reuse. To use, gently pull "plug" and begin to use material. If plug breaks, leaving the dispensing lip sealed, use a paper clip or other wire object to remove and loosen the remainder of the cured material.



1	0	0	B
HEALTH	FLAMMABILITY	REACTIVITY	PERSONAL PROTECTION
HMIS RATING			



TERAND
The Maintenance Professional's Choice

**RTV
SILICONE
CAULK & SEALANT**
CLEAR
11707

Seals, Bonds, Insulates

Flexible • Easy to Use

Waterproof • Weatherproof

100% RTV Silicone - Industrial Strength

Flexible from -60°F to +500°F

Caulks tubs, sinks, showers and plumbing fixtures

Seals windows, doors, tile, marble

Bonds almost any material

CAUTION: CONTACT WITH UNCURED SEALANT CAUSES IRRITATION. CONTENTS UNDER PRESSURE OUTER CONTAINER IS PRESSURIZED WITH A FLAMMABLE HYDROFLUOROCARBON PROPELLANT. DO NOT REMOVE RUBBER PLUG IN BOTTOM OF CONTAINER. SEE OTHER CAUTIONS ON BACK PANEL. KEEP OUT OF REACH OF CHILDREN. NET WT. 8 OZ. (227 Grams)

TERAND
INDUSTRIES, INC.

P.O. Box 667770 • Pompano Beach, FL 33066
www.terandstore.com