

This product is not compliant for sale and use in
CA CT DE ME MD MA NH NJ NY PA VA DC IL MI OH IN.

SHAKE WELL BEFORE USING

A fast acting **PENETRANT** that quickly cuts through dirt, rust and scale to creep into parts which have become frozen by or encrusted with corrosion and oxidation. Provides a long-lasting **LUBRICANT** which loosens dirt, rust and other corrosive elements, reduces friction and will not become dry, brittle or hard. Helps dry out wet electrical gear and other water sensitive parts. Prevents surface deterioration by acting as a **DEMOISTURANT**, which, with its unique molecular film, seals out water on all treated surfaces. Preserves equipment life and efficiency, thus reducing repair and maintenance costs. Can be used on either wet or dry surfaces. A true multi-purpose spray **PROTECTANT** that provides a shield-like film against the harmful effects of moisture and corrosion.

DIRECTIONS:

TO REMOVE CORROSION: Spray liberally directly onto dirty, encrusted or corroded parts. Allow to penetrate, remove loosened scale, and then re-apply to leave a protective anti-corrosive coating.

TO DISPLACE MOISTURE: Spray electrical equipment until thoroughly saturated. For best results: Stop motion of motorized or running equipment prior to application. Restart motion once full product penetration has occurred and moisture has been driven away. Apply a light final coating to protect exterior surfaces.

TO LOOSEN FROZEN NUTS AND BOLTS: Apply liberally to frozen nuts, bolts, sliding and rotating parts. Allow to penetrate into threads. Work parts back and forth until operating smoothly. Reapply to leave a never dry, protective film. To ensure adequate protection, periodic checks should be made to determine the need for reapplication.



MADE IN THE U.S.A.

DANGER: Contains Trichloroethylene (79-01-6), White Mineral Oil (8042-47-5), Octamethylcyclotetrasiloxane (556-67-2), 2-Butoxyethanol (111-76-2), Decamethylcyclopentasiloxane (541-02-06), and Carbon Dioxide (124-38-9). Harmful or fatal if swallowed. Do not take internally. Vapor harmful. Use only in well ventilated areas. Avoid breathing vapors or spray mist. In confined spaces and poorly ventilated areas, vapors can cause unconsciousness and death. Avoid contact with eyes and skin. Exposure may cause irritation. Do not expose to heat or store at temperatures above 120°F. Do not puncture or incinerate container. **WARNING:** This product contains a chemical known to the state of California to cause cancer.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Get medical attention immediately. **IF SKIN CONTACT:** Wash with plenty of soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. If continued difficulty is experienced, seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** If conscious: Drink large amounts of water. Do not induce vomiting. Seek medical attention immediately. If unconscious: Do not attempt to give anything by mouth to an unconscious person. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



HAZARD RATING:	HEALTH	2
	FLAMMABILITY	1
	REACTIVITY	0
	PERSONAL PROTECTION	G

TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com



**PENETRANT
LUBRICANT
DEMOISTURANT
PROTECTANT
CHLORINATED**

22015

Non-Flammable Spray
Fast Penetrating Action
High Dielectric Strength

DANGER: VAPOR HARMFUL.
HARMFUL OR FATAL IF SWALLOWED.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.
NET WT. 15 OZ. (425 Grams)