



FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

Contains Isoparaffinic Hydrocarbon (64742-46-7), Mineral Oil (8042-47-5), Dipropylene Glycol Monomethyl Ether (34590-94-8).

DANGER: Do not take internally. Use only in a well ventilated area. Avoid contact with eyes or prolonged contact with skin. Avoid contamination of food. Do not expose to heat or store at temperatures above 120°F.

FIRST AID:

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Get medical attention immediately.

IF SKIN CONTACT: Wash with plenty of soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. If continued difficulty is experienced, seek medical attention immediately. If breathing stops give artificial respiration.

IF INGESTED: Seek medical attention immediately.

HMS RATING: Health, 1; Flammability, 1; Reactivity, 0; Personal Protection, B.

HANDLING AND STORAGE:

Keep container closed except when in use. Do not store in unmarked containers. Store in a cool, dry place.

For further information, consult Material Safety Data Sheet.



NUT and BOLT LOOSENER

221 305

- Non-Flammable
- Non-Conductive
- Penetrates Through Rust

DANGER:
VAPOR HARMFUL
KEEP OUT OF REACH OF CHILDREN
SEE OTHER CAUTIONS ON SIDE PANEL

NET CONTENTS: 5 GALLONS



P.O. Box 667770 • Pompano Beach, FL 33066
www.terandstore.com

**NO Chlorinated Solvents
(NO 1,1,1-Trichloroethane)
(NO Perchloroethylene)
(NO Methylene Chloride)**

HIGH DIELECTRIC STRENGTH

A non-flammable nut and bolt loosener that quickly penetrates thru rust and corrosion to free frozen or rusted parts. Leaves a non-drying residual film to block out future rust and corrosion.

DIRECTIONS:

Saturate parts and area of contact. Allow to set for several minutes before attempting to break free. For parts that will not release or are heavily encrusted, the aid of a wire brush may be needed. To ensure ease of removal in the future, coat parts while reassembling and make periodic checks to determine need for reapplication.