

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

DANGER: Contains Isoparaffinic Hydrocarbon (64742-46-7), Mineral Oil (8042-47-5), Dipropylene Glycol Monomethyl Ether (34590-94-8). Do not take internally. Use only in a well ventilated area. Avoid contact with eyes or prolonged contact with skin. Avoid contamination of food. Do not expose to heat or store at temperatures above 120°F.

FIRST AID:

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Get medical attention immediately.

IF SKIN CONTACT: Wash with plenty of soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. If continued difficulty is experienced, seek medical attention immediately. If breathing stops give artificial respiration.

IF INGESTED: Seek medical attention immediately.

HMIS RATING: Health, 1; Flammability, 1; Reactivity, 0; Personal Protection, B.

HANDLING AND STORAGE:

Keep container closed except when in use. Do not store in unmarked containers. Store in a cool, dry place.

For further information, consult Material Safety Data Sheet.



MOISTURE DISPLACER

221 605

Non-Chlorinated

Dries Electrical Components

Protects Against Water Damage

Non-Flammable

Non-Conductive

39,000 Volt Dielectric Strength

DANGER:
VAPOR HARMFUL.
KEEP OUT OF REACH OF CHILDREN.
SEE OTHER CAUTIONS ON SIDE PANEL.

NET CONTENTS: 5 GALLONS

TERAND
INDUSTRIES, INC.

P.O. Box 667770 • Pompano Beach, FL 33066
www.terandstore.com

NO Chlorinated Solvents
(NO 1,1,1-Trichloroethane)
(NO Perchloroethylene)
(NO Methylene Chloride)

HIGH DIELECTRIC STRENGTH

MOISTURE DISPLACER — Displaces moisture from electrical parts. Prevents malfunction to electrical equipment exposed to high humidity.

ANTI-CORROSIVE COATING — Leaves a protective film that seals out future rust, corrosion and the harmful effects of moisture.

NUT and BOLT LOOSENER — Rapidly penetrates through rust and corrosion.

LUBRICANT — Assures free and easy movement of parts.

USES: Motors, relays, switches, plugs, reostats, electronic and electrical assemblies, parking and water meters, marine equipment, vending machines, vehicles, appliances, tools, machinery, generators, batteries, chargers, jigs, fixtures, fans, battery terminals, motorcycles, blowers, hoists, overhead doors.

DIRECTIONS:

1. For best performance and fullest protection, first clean object with degreaser solvent to remove grease, oil and debris. This will prevent material from becoming contaminated, especially when used in a dip tank.
2. Apply as a spray, brush on, or use in a dip tank.
3. Allow wetted-out rusted parts to be immersed in solution for several minutes.
4. Always keep container closed to prevent evaporation or contamination.