



This product is not compliant for sale and use in CA CT DE ME MD MA NH NJ NY PA VA DC IL MI OH IN.

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

DANGER: Contains Trichloroethylene (79-01-6), Mineral Oil (8042-47-5), Ethylene Glycol Monobutyl Ether (111-76-2), Octamethylcyclotetrasiloxane (556-67-2) and Decamethylcyclopentasiloxane (541-02-6). Use only in a well-ventilated area with a constant supply of fresh air. Avoid breathing vapors. Excessive inhalation of vapors may cause nasal and respiratory irritation and central nervous system depression effects including dizziness, nausea and headaches. In confined or poorly ventilated areas, vapors can cause unconsciousness or death. If you experience eye watering, headaches or dizziness, increase airflow, wear respiratory protection or leave the area. Avoid eye contact and excessive skin contact. Do not expose to heat or store at temperatures above 120°F. **WARNING:** This product contains a chemical known to the state of California to cause cancer.

FIRST AID:

IF EYE CONTACT: Flush with water for 15 minutes, lifting upper and lower lids. Get medical attention immediately.

IF SKIN CONTACT: Remove contaminated clothing. Wash off affected skin with soap and water. If irritation persists get medical attention.

EXCESSIVE INHALATION: Remove victim to fresh air and call a physician immediately.

IF INGESTED: Do not induce vomiting. Get medical attention immediately.

HMS RATING: Health, 2; Flammability, 0; Reactivity, 0; Personal Protection, G.

HANDLING AND STORAGE:

Keep container closed except when in use. Do not store in unmarked containers. Store in a cool, dry place.

For additional information, consult Material Safety Data Sheet.



PENETRANT LUBRICANT DEMOISTURANT PROTECTANT CHLORINATED

222005

Non-Flammable

Non-Conductive

DANGER:
VAPOR HARMFUL
HARMFUL OR FATAL IF SWALLOWED
SEE OTHER CAUTIONS ON SIDE PANEL

NET CONTENTS: 5 GALLONS



P.O. Box 667770 • Pompano Beach, FL 33066
www.terandstore.com

HIGH DIELECTRIC STRENGTH

NUT and BOLT LOOSENER — Rapidly penetrates through rust and corrosion.

WATER DISPLACER — Displaces moisture from electrical parts. Prevents malfunction to electrical equipment exposed to high humidity.

LUBRICANT — Assures free and easy movement of parts.

ANTI-CORROSIVE COATING — Leaves a protective film that seals out future rust, corrosion and the harmful effects of moisture.

USES: Motors, relays, switches, plugs, reostats, electronic and electrical assemblies, parking and water meters, marine equipment, vending machines, vehicles, appliances, tools, machinery, generators, batteries, chargers, jigs, fixtures, fans, battery terminals, motorcycles, blowers, hoists, overhead doors.

DIRECTIONS:

1. For best performance and fullest protection, first clean object with degreaser solvent to remove grease, oil and debris. This will prevent material from becoming contaminated, especially when used in a dip tank.
2. Apply as a spray, brush on, or use in a dip tank.
3. Allow wetted-out rusted parts to be immersed in solution for several minutes.
4. Always keep container closed to prevent evaporation or contamination.