

This product is not compliant for sale and use in
 CA CT DE ME MD MA NH NJ NY PA VA DC IL MI OH IN.

A non-flammable nut and bolt loosener that quickly penetrates through rust and corrosion to free frozen or rusted parts. Leaves a non-drying residual film to block out future rust and corrosion.

DIRECTIONS:

Saturate parts and area of contact. Allow to set for several minutes before attempting to break free. For parts that will not release or are heavily encrusted, the aid of a wire brush may be needed. To ensure ease of removal in the future, coat parts while reassembling and make periodic checks to determine need for reapplication.



DANGER: Contains Trichloroethylene (79-01-6), White Mineral Oil (8042-47-5), Octamethylcyclotetrasiloxane (556-67-2), 2-Butoxyethanol (111-76-2), Decamethylcyclopentasiloxane (541-02-06), and Carbon Dioxide (124-38-9). Harmful or fatal if swallowed. Do not take internally. Vapor harmful. Use only in well ventilated areas. Avoid breathing vapors or spray mist. In confined spaces and poorly ventilated areas, vapors can cause unconsciousness and death. Avoid contact with eyes and skin. Exposure may cause irritation. Do not expose to heat or store at temperatures above 120°F. Do not puncture or incinerate container. **WARNING:** This product contains a chemical known to the state of California to cause cancer.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Get medical attention immediately. **IF SKIN CONTACT:** Wash with plenty of soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

HMIS RATING	HEALTH	2
	FLAMMABILITY	1
	REACTIVITY	0
	PERSONAL PROTECTION	G

KEEP OUT OF REACH OF CHILDREN



TERAND INDUSTRIES, INC.

P.O. Box 667770
 Pompano Beach, FL 33066
 www.terandstore.com



NUT and BOLT LOOSENER CHLORINATED
 22215

Fast-Acting, Penetrating Formula For Loosening Rusted Parts

Frees Frozen Nuts & Bolts

Non-Flammable Spray

Dielectric Strength: 38,000 Volts

DANGER: VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 15 OZ. (425 Grams)