

***SPECIALLY FORMULATED WITH NO FLAMMABLE ELEMENTS**

A high purity freezing agent for electronic application. Allows isolation of single components in low temperature electronic testing. Protects expensive components during soldering or desoldering and non-destructive testing of electronic and electro-mechanical systems. Quickly cools thermostats for activation and testing. A highly efficient localized heat sink for assembly of electronic circuits. Instantly chills small pins, shafts, bushings, bearings, etc., for precision shrink-fitting.

DIRECTIONS:

Insert extension tube into actuator for pinpoint application. Spray from a close distance (1 or 2 inches) until frost appears.



MADE IN THE
U.S.A.

CAUTION: HIGH PRESSURE — DO NOT STORE IN VEHICLES — INTENTIONAL MISUSE BY INHALING CONTENTS CAN BE HARMFUL OR FATAL. Contains 1,1,1,2-Tetrafluoroethane (811-97-2). Contents under pressure. Do not puncture or incinerate container. Do not store near heat or open flame. Exposure to temperatures above 120°F may cause bursting. **USE ONLY WITH ADEQUATE VENTILATION.** Inhalation of high concentration of vapor is harmful and may cause heart irregularities, unconsciousness or death.

FIRST AID: IF EYE CONTACT: In case of contact, immediately flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Call a physician. **IF SKIN CONTACT:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Call a physician. Treat for frostbite if necessary by gently warming affected area. Wash contaminated clothing before reuse. **EXCESSIVE INHALATION:** If high concentrations are inhaled, immediately remove to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician. **IF INGESTED:** Ingestion is not considered a potential route of exposure.

HMIS RATING:	HEALTH	1
	FLAMMABILITY	0
	REACTIVITY	1
	PERSONAL PROTECTION	B

For further information consult
Material Safety Data Sheet.

**KEEP OUT OF REACH
OF CHILDREN**



TERAND
INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice

ELECTRONIC PARTS CHILLER

24106

100% Ozone Safe • 0% Voc
Completely Non-Flammable*
Quick Freezing Action • Moisture Free
Pinpoint Spray • Instant Freezing

CAUTION: CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 6 OZ. (170 Grams)