



The Maintenance Professional's Choice



FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

DANGER: Acetone (667-64-1) and Heptane, Branched, Cyclic and Linear (426260-76-6).

FIRST AID:

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

HMIS RATING: Health, 1; Flammability, 3; Reactivity, 0; Personal Protection, B.

HANDLING AND STORAGE:

Keep container closed except when in use. Do not store in unmarked containers. Store in a cool, dry place. Do not cut or weld on or near this container even when empty.

KEEP OUT OF REACH OF CHILDREN

For further information, consult Material Safety Data Sheet.



MADE IN THE U.S.A.

SILICONE LUBRICANT SUPER DRY

259305

Dry Silicone Lubricant & Mold Release

DANGER: FLAMMABLE LIQUID. VAPOR HARMFUL. KEEP OUT OF REACH OF CHILDREN. SEE OTHER CAUTIONS ON SIDE PANEL.

NET CONTENTS: 5 GALLONS



P.O. Box 667770 • Pompano Beach, FL 33066
www.terandstore.com

SUPER DRY SILICONE SPRAY is a pure silicone, quick drying, invisible coating.

SUPER DRY SILICONE SPRAY is effective over a wide temperature range -40°F to 285°F.

The film is not affected by water or oil.

Prevents build-up of glue, lint, oils, and greases on all surfaces.

Excellent as a heat stable mold release.

Improves slide and glide capabilities on metal and rubber surfaces.

SUPER DRY SILICONE SPRAY is non-staining and oil-free, which allows for extensive use in the textile and printing trades – Cutting Tables, Needles, Knife Blades, Scissors, Zippers, and Saws.

SUPER DRY SILICONE SPRAY reduces friction, stops sticking, squealing and binding of doors, windows, hinges, tracks, conveyors, chutes, molds, and sealing equipment.

DIRECTIONS:

1. Clean surface thoroughly before applying.
2. Do not thin with any other chemical.
3. May be applied by dipping or spraying.
4. When spraying, use either airless or compressed air sprayer and apply lightly and evenly.
5. Always keep container closed when not in use to prevent evaporation or contamination.