

- Blocks Out Ultra-Violet Rays
- Inhibits Cracking, Fading and Hardening of Rubber, Vinyl and Leather
- Increases Pliability • Restores Color • Odorless
- Foam Holds on Vertical Surfaces

USES: Door and window moldings, seating surfaces, armrests, shifter handles, door panels and vinyl tops.

NOTE: Protect floor mats and pedals from overspray to prevent slippery condition. Protect windows when doing vinyl tops.

DIRECTIONS: Offers a unique 360° valve which allows spraying in an upright or inverted position. Clean heavily soiled surfaces first. Spray on clean, dry surface, spread with cloth. Let set for short period so surface can be penetrated. Buff and polish with clean, dry, soft cloth or polishing pad.



MADE IN THE U.S.A.

CAUTION: Contains Polydimethylsiloxane (63148-62-9), Glycerine (56-81-5) and Liquefied Petroleum Gas (68476-85-7). Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

HMS RATING:	HEALTH	1
	FLAMMABILITY	0
	REACTIVITY	0
	PERSONAL PROTECTION	B



TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com



The Maintenance Professional's Choice

DETAILER and PROTECTOR

AUTO INTERIOR

26014

Anti-Static

Prolongs Life

For Vinyl,
Leather, Rubber,
Plastics,
Fiberglass

CAUTION:
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.
NET WT. 14 OZ. (396 Grams)