



### FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

**USES:** Heavy Equipment, Highway Signs, Machinery, Tanks, Trucks, Trailers, Automobiles, Gym Floors, Wood And Metal Furniture, Box Manufacturing Equipment, Farm Equipment, Shipyards, Marinas, Body Shops, Electric Motor Rewinding Shops, Fire Hydrants and Boxes.

**CONTAINS:** Methylene Chloride (75-09-2), Toluene (108-88-3), Ethanol (64-17-5) and Methanol (67-56-1).

**DANGER:** Do not take internally. Avoid contact with eyes. Avoid breathing vapors. Keep away from heat, sparks and open flame.

#### FIRST AID:

**IF EYE CONTACT:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

**IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention.

**EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

**IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

**HMIS RATING:** Health, 3; Flammability, 3; Reactivity, 1; Personal Protection, H.

#### HANDLING AND STORAGE:

Keep container closed except when in use. Do not store in unmarked containers. Store in cool, dry place. Do not cut or weld on or near container even empty.

For further information, consult Material Safety Data Sheet.



# PAINT STRIPPER

276005

Gel-Type  
Fast Blistering Action  
Scrape Or Flush Off

**DANGER:**  
FLAMMABLE.  
VAPOR HARMFUL.  
KEEP OUT OF REACH OF CHILDREN.  
SEE OTHER CAUTIONS ON SIDE PANEL.  
NET CONTENTS: 5 GALLONS



P.O. Box 667770 • Pompano Beach, FL 33066  
www.terandstore.com

A fast acting, water emulsifiable paint and varnish remover. Sprays as a gel that clings to vertical surfaces without running. Deep penetrating action breaks the bond of the finish, making the removal of difficult finishes faster.

Non-corrosive to substrate while removing lacquers, enamels, shellacs, acrylics, etc. Usable on plaster, masonry, stone, wood, metal, glass, or ceramics. Contains no acids or alkalis.

#### DIRECTIONS:

1. Clean off heavy oil or grease with detergent and water and allow to dry.
2. Apply a heavy coating with sprayer, inexpensive brush or a lambs wool applicator.
3. Allow to remain on the surface until surface is heavily wrinkled or blistered.
4. Hose off with water under pressure or remove by scraping.
5. If re-application is necessary, be sure surface is dry. It is not necessary to neutralize stripped surfaces before painting, however, be sure the surface is completely clean and dry.
6. May be used in a SOAK TANK fitted with a tight cover.
7. GYM SEALS: Apply a heavy coat in one direction at the rate of 50-100 sq. ft. per gal. Immediately after application, sprinkle coarse sawdust over treated surface to retard evaporation. Allow to set until surface is heavily wrinkled, then use a wire brush or steel wool to work absorbing sawdust down into old finish. Sweep away the dry residue after brushing.
8. Always keep container closed when not in use to avoid evaporation or contamination.
9. Do not mix with other chemicals.