



This product is not compliant for sale and use in CA CT DE ME MD MA NH NJ NY PA VA DC IL MI OH IN.

**FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY**

**CONTAINS:** Methylene Chloride (75-09-2), Toluene (108-88-3) and Methanol (67-56-1).

**DANGER:** Do not take internally. Avoid contact with eyes. Avoid breathing vapors. Keep away from heat, sparks and open flame.

**FIRST AID:**

**IF EYE CONTACT:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

**IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention.

**EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

**IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

**HMS RATING:** Health, 3; Flammability, 4; Reactivity, 1; Personal Protection, H.

**HANDLING AND STORAGE:**

Keep container closed except when in use. Do not store in unmarked containers. Store in a cool, dry place. Do not cut or weld, on or near container, even when empty.

For further information, consult Material Safety Data Sheet.



# GASKET and DECAL REMOVER

276505

Gel-Type  
Fast Blistering Action  
Scrape or Flush Off

**DANGER:**  
FLAMMABLE. VAPOR HARMFUL.  
KEEP OUT OF REACH OF CHILDREN.  
SEE OTHER CAUTIONS ON SIDE PANEL.

NET CONTENTS: 5 GALLONS



P.O. Box 667770 • Pompano Beach, FL 33066  
www.terandstore.com

A fast acting, water emulsifiable gasket and decal\* remover.

Sprays as a gel that clings to vertical surfaces without running. Deep penetrating action breaks the bond of the adhesive to the surface for easy removal without grinding, sanding, soaking or heating.

Non-corrosive to substrate. Leaves surface smooth and clean and ready for new gasket or painting. Contains no acids or alkalies.

**DECAL REMOVER USES:** Auto and Truck Body Refinishing, Removal of Decal Stickers from fleet operations, Removes Stickers from Refillable Gas Cylinders

\*DECAL REMOVAL ONLY WHEN STRIPPING DOWN TO BARE METAL SURFACE

**DIRECTIONS:**

1. Clean off heavy oil or grease with detergent and water and allow to dry.
2. Apply a heavy coating with sprayer, inexpensive brush or a lambs wool applicator.
3. Allow to remain on the surface until surface is heavily wrinkled or blistered.
4. Hose off with water under pressure or remove by scraping.
5. If re-application is necessary, be sure surface is dry. It is not necessary to neutralize stripped surfaces before painting, however, be sure the surface is completely clean and dry.
6. Always keep container closed when not in use to avoid evaporation or contamination.
7. Do not mix with other chemicals.