



### FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

**DANGER:** Copper Compound (7440-50-8). Do not take internally. Avoid contact with eyes. Avoid breathing vapors. Vapor is heavier than air and may collect in low lying areas.

#### FIRST AID:

**IF EYE CONTACT:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Get medical attention immediately.

**IF SKIN CONTACT:** Wash with plenty of soap and water. If irritation persists seek medical attention.

**EXCESSIVE INHALATION:** Remove to fresh air.

**IF INGESTED:** Seek medical attention immediately.

**HMIS RATING:** Health, 1; Flammability, 0; Reactivity, 1; Personal Protection, B.

#### HANDLING AND STORAGE:

Keep container closed except when in use. Do not store in unmarked containers. Store in cool, dry place. Do not cut or weld on or near container even when empty.

#### KEEP OUT OF REACH OF CHILDREN

For further information consult  
Material Safety Data Sheet



# ANTI-SEIZE COMPOUND

279005

Extreme Temperature and  
Extreme Pressure Lubricant

Non-Melting

Non-Hardening

**DANGER:**  
HARMFUL OR FATAL IF SWALLOWED.  
KEEP OUT OF REACH OF CHILDREN.  
SEE OTHER CAUTIONS ON SIDE PANEL.

NET CONTENTS: 5 GALLONS

**TERAND**  
INDUSTRIES, INC.

P.O. Box 667770 • Pompano Beach, FL 33066  
www.terandstore.com

### PREVENTS GALLING – SEIZING GALVANIC ACTION – PITTING AND THREAD DISTORTION

WILL NOT WASH OFF – NON-MELTING  
WILL NOT EVAPORATE,  
SEPARATE or HARDEN  
WILL NOT FUSE TO METALS

Provides long-term protection even when exposed to steam. Alkalis dilute acids, damp atmospheres and salt spray. Protects metal parts under sustained temperatures up to 2100°F (1050°C). ANTI-SEIZE COMPOUND acts as a sealant, reduces friction, makes tighter, firmer joints that open easier reducing torque requirements. Inert to rubber, reduces wear and friction from metal-to-metal and metal to rubber parts.

**USEFUL ON THESE SURFACES:** Cast Iron, Steel, Steel Alloys, Aluminum, Copper, Brass, Titanium, Rubber (Natural and Synthetic).

**USE ON:** Assemblies, Bearings, Belts, Bolts, Bushings, Cables, Cams, Chains, Clamps, Converters, Conveyor Systems, Couplers, Cover Plates, Drive Chains, Engine Heads, Fittings, Gears, Flanges, Gaskets, Gear Boxes, Hose Connections, Joints, Latches, Nuts, O-Rings, Pins, Pillow Blocks, Pipes, Pipe Fittings, Plugs, Press Fittings, Pumps, Rim Locking Rings, Rods, Roller Pins, Screws, Shafts and Hubs, Slide Rails, Splines, Speed Reducers, Valves, Thermocouples, Threaded Areas, Trolleys, U-Joints.

#### DIRECTIONS:

1. Clean surface of dirt, rust, grease or oil.
2. Use with a grease gun or pressure pump. If pressure pump is used, be sure drum is fitted with "Follower Plate." Can be applied with a brush.
3. Keep container closed when not in use to prevent evaporation or contamination.