

CONFORMS TO TESTS SPECIFIED IN ASTM STP 332

Contains no silicones or chlorinated solvents which affect plastics, lacquers, insulation and paint. Contains Molybdenum disulfide and polytetrafluoroethylene for added pressure and wear resistance.

Forceful jet-spray aids in rapid penetration through rust and corrosion to free frozen parts. Leaves a long-lasting, lubricating film which defends against future corrosion.

Provides effective lubrication over a broad range of temperatures and pressures.

***NOTE: SPECIAL VALVE ALLOWS CAN TO BE SPRAYED WHILE HELD IN ANY POSITION.**

DIRECTIONS:

Saturate part and allow to stand for a few minutes before attempting to break free. For heavily encrusted parts a wire brush may be needed. Apply a light spray to parts prior to reassembly.



MADE IN THE U.S.A.

DANGER: Contains Mineral Oil (8042-47-5), Aliphatic Hydrocarbons (8052-41-3), Liquefied Petroleum Gas (68476-86-8), and Propylene Glycol Monomethyl Ether (107-98-2). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes and prolonged contact with skin. Do not permit product to contaminate tobacco products. Wash hands before smoking. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



HMIS RATINGS	HEALTH	1
	FLAMMABILITY	2
	REACTIVITY	0
	PERSONAL PROTECTION	B

TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com



PENETRATING LUBRICANT WITH PTFE

50111

Fortified with Moly & PTFE for Added Pressure and Wear Resistance

Contains No Silicones or Chlorinated Solvents

Quickly Cuts Through Rust and Corrosion

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 11 OZ. (311 Grams)