

**HIGH VISCOSITY
CONTAINS NO CFC's or CHLORINATED SOLVENTS**

A pure, non-staining super dry, heavy duty, multi-purpose silicone lubricant. Safe for use on almost any surface. Reduces friction and annoying squeaks in hinges, latches, springs, gears and other mechanisms.

The high-silicone formula is excellent for use to prevent corrosion on metal, to reduce friction and wear, and quiet moving parts.

Provides a water and weather-resistant barrier that protects surfaces from corrosion and wear. Virtually odorless and colorless when dry.

USED BY: Industrial plants, printing Industry, garment and textile industry, packaging plants, molding and cutting operations, shipping and package handling operations, construction and maintenance crews.

DIRECTIONS:

SHAKE WELL BEFORE USING. Spray onto clean surface from a distance of four to six inches. Silicone film dries almost instantly. No need to wipe. Cover floors with paper as overspray on floors may cause slippery conditions.



MADE IN THE
U.S.A.

DANGER: Contains Liquefied Petroleum Gas (68476-86-8), Acetone (67-64-1), and Heptane (426260-76-6). May irritate eyes, skin, and respiratory passages. Use only in a well ventilated area. Avoid contact with eyes or prolonged contact with skin. Do not use near heat, sparks, or open flame. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

For further information consult
Material Safety Data Sheet.

**KEEP OUT OF REACH
OF CHILDREN**



HMIS RATINGS	HEALTH	1
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	B

**TERAND
INDUSTRIES, INC.**

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com



**SILICONE
LUBRICANT
SUPER DRY**
5931 1

Dries Instantly

Non-Staining

Safe on Plastic

Heavy-Duty

Multi-Purpose

Dry Film Stable from
-40°F to +285°F

DANGER: EXTREMELY FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 11 OZ. (311 Grams)