

Contains **NO Chlorinated Solvents**
(**NO 1,1,1-Trichloroethane**)
NO Hexane • NO CFC's
MEETS MIL SPEC TT-C-520-A

Provides a durable, flexible, rubberized film which is impervious to water and forms a tough rubberized coating that seals out rust and corrosion on air conditioning pans while reducing unwanted vibration and sound.

OTHER USES: Reduces squeaks and noise of ducts, metal walls, metal sinks, plastic piping, seals tree-pruning wounds, seals electrical junction boxes from dust, water and fumes.

DIRECTIONS:

SHAKE WELL UNTIL BALL RATTLES FREE. Apply to a clean, dry surface. Do not use if temperature of can is below 60°F. Spray surface with short, even strokes from a distance of 12 to 14 inches. Several thin coats are better than one heavy coat.



DANGER: Contains Liquefied Petroleum Gas (68476-86-8), Toluene (108-88-3), Aliphatic Petroleum Distillate (8052-41-3), Aliphatic Petroleum Solvent (64742-89-8), Calcium Carbonate (1317-65-3) and Carbon Black (1333-86-4). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



HMIS RATING:	HEALTH	2
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	C

TERAND
INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice

CONVECTOR PAN SEALANT

64114

Non-Chlorinated

Seals Out Rust &
Corrosion

Rubberized Flexible
Coating

DANGER:
EXTREMELY FLAMMABLE.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 14 OZ. (396 Grams)