

**EFFECTIVE ON METALS, WOOD,
ROOFING MATERIALS, TIN, CONCRETE, ETC.
STAYS PLIABLE IN WINTER COLD
WILL NOT SAG, MELT OR DRIP IN THE SUMMER HEAT
RESISTS CRACKING, PEELING AND ABRASION
EASY TO APPLY, REDUCES CLEAN-UP**

Provides a super-thick, black, durable and flexible rubberized film. Reduces unwanted sound and vibration.

USED BY: Roofing Contractors, Air Conditioner Installers, Maintenance Crews, Building Supers, Construction Crews, and Plumbers.

FOR USE ON: Overlapping Seams, Gravel Stops, Chimney and Skylight Flashing, Vents and Pipe Flashing, Mobile Home and Camper Roof Seams, A/C Drip Pans, Gutters, Below-Grade Foundations, Minor Leak Repair.

DIRECTIONS:

SHAKE WELL UNTIL BALL RATTLES FREE

Apply to a clean, dry surface. Do not use if temperature of can is below 60°F. Spray surface with short, even strokes from a distance of 12 to 14 inches. Several thin coats are better than one heavy coat.



DANGER: Contains Liquefied Petroleum Gas (68476-86-8), Toluene (108-88-3), Aliphatic Petroleum Distillate (8052-41-3), Aliphatic Petroleum Solvent (64742-89-8), Calcium Carbonate (1317-65-3) and Carbon Black (1333-86-4). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. **WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

HMS RATING:	HEALTH	2
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	C

TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice

RUBBERIZED COATING

64414

Protects Metal Surfaces
Against Corrosion

Provides a Flexible,
Water-Tight Film

Reduces Unwanted Sound
and Vibration

Effective Over a
Wide Temperature Range

DANGER: EXTREMELY FLAMMABLE.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 14 OZ. (396 Grams)