

Contains NO Chlorinated Solvents
NO 1,1,1-Trichloroethane

NO Hexane • NO CFC's

FAST • CONVENIENT • EASY TO USE
NO STIRRING • NO POURING
NO BRUSHES TO CLEAN

A thick, black coating developed for sealing all kinds of tree wounds and pruning stubs. Helps prevent fungus growth and insect infestation. The rubberized coating will not sag, crack or peel and stays pliable in all types of weather conditions. Used extensively by yard men, lawn services, ground crews and tree surgeons. Excellent for sealing small cavities, and also as an overcoat for tree wraps.

Read all instructions before using this product

DIRECTIONS:

SHAKE WELL. Shake vigorously until agitator ball inside can rattles freely for one minute. Shake can occasionally throughout application. Spray surface using a sweeping motion from a distance of 12 to 14 inches. For maximum effectiveness, apply several thin coats rather than one thick layer. For best results, use only at can-temperatures above 60°F.

NOTE: After each use, invert can and apply a short burst to clear actuator.



DANGER: Contains Toluene (108-88-3), Aliphatic Petroleum Distillate (8052-41-3), Aliphatic Petroleum Solvent (64742-89-8), Calcium Carbonate (1317-65-3) and Liquefied Petroleum Gas (68476-86-8). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. **WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

HMS RATING:	HEALTH	2
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	C

TERAND
INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice

TREE WOUND SPRAY

64514

Seals – Heals

Helps Prevent Disease & Insect Infestation

Provides A Thick, Black, Rubberized Bandage

DANGER: EXTREMELY FLAMMABLE.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 14 OZ. (396 Grams)