

This product is not compliant for sale and use in CA CT DE ME MD MA NH NJ NY PA VA DC IL MI OH IN.

DIRECTIONS:

SHAKE VIGOROUSLY BEFORE EACH USE. Clean off dirt, grease or heavy oil. Make certain surface is dry. Hold can 8 to 10 inches from surface. Apply a heavy, even coat to entire surface. Allow product to remain on surface for several minutes, even after blistering action has occurred.

FOR GASKETS: Put putty knife under edge and peel up. Second application may ease removal of remaining cement.

FOR DECALS: Scrape, wipe or flush off with water.

***NOTE: DISSOLVES PAINT—** Remove decals from painted surfaces only when repainting is planned.

If necessary, repeat application after surface is dry. Clean valve by turning can upside down and applying a short burst.

PRETESTING: Test product in small inconspicuous area before application.



WARNING: Protect surrounding objects from overspray. Solvent will attack paint, rubber, plastics, asphalt tile and many synthetic materials. Do not allow scrapings or washings to contact food or live vegetation. Use of chemical resistant gloves is recommended, especially if skin is subject to allergy or rash. Avoid contact with or inhalation of spray mist.

DANGER: Contains Methylene Chloride (75-09-2), Liquefied Petroleum Gas (68476-85-7), Toluene (108-88-3), Ethanol (64-17-5) and Methanol (67-56-1). Cannot be made nonpoisonous. Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes and skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

FIRST AID: IF EYE

CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

IF SKIN

CONTACT: Wash with soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION:

Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

IF

INGESTED: Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

HMIS RATING:	HEALTH	3
	FLAMMABILITY	3
	REACTIVITY	1
	PERSONAL PROTECTION	H

KEEP OUT OF REACH OF CHILDREN



TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com



GASKET and DECAL REMOVER

76518

For Cork, Rubber, Felt, Paper, Metal and Composite Gaskets

Vinyl, Poly and Plastic Film Decals and Stickers

Spray On — Scrape Off

DANGER: EXTREMELY FLAMMABLE. MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. VAPOR HARMFUL. CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 18 OZ. (1 LB. 2 OZ.) (510 Grams)