

**SHAKE WELL BEFORE USE**  
**DO NOT SPRAY WHEN COLD**  
**MAY CAUSE CLOGGING OF SPRAY TIP**

**REPAIRS:** Popcorn Ceilings, Knockdown Textures, Orange Peel Finish and Drywall.

Specially designed to repair dings, scrapes, runs, holes and gouges in popcorn and sprayed on plaster ceilings. Dries quickly to a clean, white, rough surface that can be painted after drying. The coating adheres to many surfaces. Ideal for blending all types of tubes or pipes which connect ceiling fans and other electrical devices or plumbing. When used as directed, provides and invisible ceiling repair.

**DURABLE • FLEXIBLE • WATER RESISTANT**  
**MAY BE PAINTED WHEN DRY**

**PREPARATION:** Remove loose dust and dirt by wiping surface gently with a dry rag or duster. Cover surfaces under area to be treated with newspaper or a drop cloth. Protect other areas with masking tape.

**DIRECTIONS:**

**SHAKE VIGOROUSLY BEFORE AND DURING USE.** Shake can vigorously until agitator ball rattles freely. Continue shaking for at least one minute. Shake occasionally during use. **FOR TEXTURED EFFECTS:** Spray surface from a distance of 8 to 10 inches. Apply several thin coats with a sweeping motion. Repeat until desired thickness is obtained. **FOR PATCHING CRACKS:** Use included extension tip and tube. Apply to surface with short bursts from a distance of 2 to 3 inches. Remove tube and spray area with a light coating to "feather" or blend repair into surrounding area. **IMPORTANT:** After application, clean valve by turning can upside down and applying short burst to clear actuator.



**MADE IN THE U.S.A.**

**DANGER:** Contains Trichloroethylene (79-01-6), Liquefied Petroleum Gas (68476-85-7), Stearic Acid (57-11-4), Parachlorobenzotrifluoride (98-56-6), and Titanium Dioxide (13463-67-7). Use only in a well ventilated area with a constant supply of fresh air. Avoid breathing vapors or spray mist. Excessive inhalation of vapors may cause nasal or respiratory irritation and central nervous system effects including dizziness, nausea and headaches. In confined or poorly ventilated areas, vapors can cause unconsciousness. If you experience eye watering, headaches or dizziness, increase air flow, wear respiratory protection or leave the area. Avoid eye contact and excessive skin contact. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. **WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**FIRST AID: IF EYE CONTACT:** Flush with large amounts of cool water for 15 minutes, lifting upper and lower lids. Get immediate medical attention. **IF SKIN CONTACT:** Wash affected area immediately with soap and water. If irritation persists, get medical attention. **EXCESSIVE INHALATION:** Remove to fresh air and call a physician. **IF INGESTED:** Do not induce vomiting. Get immediate medical attention.

For further information consult Material Safety Data Sheet.

**KEEP OUT OF REACH OF CHILDREN**

<b>HMS RATING:</b>	<b>HEALTH</b>	<b>2</b>
	<b>FLAMMABILITY</b>	<b>2</b>
	<b>REACTIVITY</b>	<b>1</b>
	<b>PERSONAL PROTECTION</b>	<b>B</b>

**TERAND INDUSTRIES, INC.**

P.O. Box 667770  
 Pompano Beach, FL 33066  
 www.terandstore.com



# POPCORN CEILING PATCH

77215

Ceiling White

Non-Flammable When Dry

For Sprayed On,  
 Knockdown, Textured,  
 Plastered and Popcorn Type  
 Ceilings

**DANGER: EXTREMELY FLAMMABLE.**  
 VAPOR HARMFUL.  
 CONTENTS UNDER PRESSURE.  
 SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 15 OZ. (425 Grams)