

OPEN GEAR LUBRICANT is a tacky spray lubricant that protects all moving metal surfaces from metal to metal contact. Forms a protective water-resistant coating to prevent corrosion in outdoor applications.

OPEN GEAR LUBRICANT provides an elastic retractable film that reappplies itself with each revolution or movement of the lubricated part.

OPEN GEAR LUBRICANT penetrates into gears and cables where it sets up and bonds a Molybdenum Disulfide shield to parts, maintaining a cushion of lubricant between gear teeth and other friction-producing surfaces. Absorbs high shock loads, extreme pressure and prevents chipping and scuffing. Will not wash off, dry out, crack or peel.

USE ON: Passenger and freight elevators, drag lines, construction, mining, dredging and earth moving equipment; textile and steel mill machinery, winches, cranes, tugboats, offshore drilling rigs, snow removal equipment and wherever an underwater lubricant is needed.

Read all instructions before using this product.

DIRECTIONS: SHAKE WELL.

Shake vigorously until agitator ball inside can rattle freely for one minute. Shake can occasionally throughout application.



DANGER: Contains Liquefied Petroleum Gas (68476-86-8) and Trichloroethylene (79-01-06). Use only in a well ventilated area with a constant supply of fresh air. Avoid breathing vapors or spray mist. Excessive inhalation of vapors may cause nasal and respiratory irritation and central nervous system effects including dizziness, nausea and headaches. In confined or poorly ventilated areas, vapors can cause unconsciousness or death. If you experience eye watering, headaches or dizziness, increase air flow, wear respiratory protection or leave the area. Avoid eye contact and excessive skin contact. Do not expose to heat or store at temperatures above 120 F. Do not puncture or incinerate container. **WARNING:** This product contains a chemical known to the State of California to cause cancer.

For further information consult Material Safety Data Sheet.



FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

KEEP OUT OF REACH OF CHILDREN

HMS RATING:	HEALTH	2
	FLAMMABILITY	1
	REACTIVITY	0
	PERSONAL PROTECTION	G

TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice

OPEN GEAR LUBRICANT

78014

Fast Tacking Formula
Prevents Sling-Off

Contains Moly to Reduce
Wear from Metal-to-Metal
Contact

Recoats with Each Revolution

DANGER: EXTREMELY FLAMMABLE.
VAPOR HARMFUL. CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 14 OZ. (396 Grams)