

**Contains No Chlorinated Solvents  
(No 1,1,1-Trichloroethane)**

Prevents galling, seizing, pitting, fretting, corrosion and distortion of threaded, keyed, splined and press fitted assemblies. Protects at sustained temperatures of up to 2100°F. Highly resistant to moisture, weather, chemical fumes, salt spray and steam. Allows tighter, more vibration-proof seals using less torque while making disassembly easier.

**USE ON:** Industrial machinery, construction, farm, mining and earth moving equipment, marine hardware, vehicle fleets and assembly lines.

**DIRECTIONS:**

Preclean surfaces to be treated, removing any old contaminated grease, dirt or grit. Shake can thoroughly until agitator ball begins to rattle freely for at least 30 seconds. With can held in upright position, spray surface in short bursts from a distance of 8 to 10 inches. After use, invert can and clear actuator by spraying until only gas is dispelled.



MADE IN THE U.S.A.

**DANGER:** Contains Liquefied Petroleum Gas (68476-86-8), Acetone (67-64-1), Copper Compound (7440-50-8), Isoparaflinic Hydrocarbon (64742-47-8) and Isoparaflinic Hydrocarbon (64741-66-8). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

**FIRST AID: IF EYE CONTACT:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

**KEEP OUT OF REACH OF CHILDREN**



<b>HAZARD RATING:</b>	<b>HEALTH</b>	<b>1</b>
	<b>FLAMMABILITY</b>	<b>3</b>
	<b>REACTIVITY</b>	<b>1</b>
	<b>PERSONAL PROTECTION</b>	<b>B</b>

**TERAND INDUSTRIES, INC.**

P.O. Box 667770  
Pompano Beach, FL 33066  
www.terandstore.com



# ANTI-SEIZE COMPOUND

79012

Non-Chlorinated

Extreme Temperature And  
Extreme Pressure Lubricant

**DANGER:** EXTREMELY FLAMMABLE.  
HARMFUL OR FATAL IF SWALLOWED.  
CONTENTS UNDER PRESSURE.  
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 12 OZ. (340 Grams)