

This product is not compliant for sale and use in
 CA CT DE ME MD MA NH NJ NY PA VA DC IL MI OH IN.

DESCRIPTION:

- QUICK-DRYING, HIGH-PURITY FORMULA evaporates rapidly and leaves no residue.
- SAFE FOR USE on most plastics and paints.
- INCREASES PERFORMANCE, prolongs equipment life and prevents electrical failures by dissolving light oils, flux, dirt and fingerprints on contacts, relays, switches, circuits and PC boards.

DIRECTIONS:

Read entire label before using this product.

1. Shut off power supply. Be sure all stored power is drained from system and allow hot surfaces to cool before using product.
2. For optimum results, prepare heavily soiled or corroded surfaces by buffing with mild abrasive or spray with Air Duster.
3. Tilt surface and spray until clean.
4. Use an intermittent spray to dislodge trapped particles and allow excess cleaner to run off.
5. Use extension tube for pinpoint delivery or hard-to-reach areas.
6. Allow product to dry completely and thoroughly vent system before restoring power.
7. For personal safety, do not apply while equipment is energized.



MADE IN THE U.S.A.

DANGER: Contains Isohexanes (107-83-5), n-Hexane (110-54-3), Petroleum Distillate (64742-48-9), Carbon Dioxide (124-38-9) and Methanol (67-56-1). Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Product is extremely flammable; do not use on energized equipment and keep away from flames or other ignition sources. Use only in well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to the vapor may cause irritation to eyes, respiratory tract, headaches, dizziness, drowsiness, anesthesia, unconsciousness and other central nervous system effects. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Vapors are heavier than air and collect in low areas.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations.

ELECTRICAL SHOCK HAZARD: This can and its contents will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and / or electrical shock.

KEEP OUT OF REACH OF CHILDREN



FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Remove contaminated clothing. Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

SPECIAL USAGE WARNINGS: Contents extremely flammable • Do not smoke while spraying • Extinguish all flames, pilot lights and heaters. • Do not apply while equipment is energized. • Vapors will accumulate readily and may ignite. • Use only with adequate ventilation. • Maintain ventilation during use and until vapors are gone.

For further information consult Material Safety Data Sheet.

HMIS RATING:	HEALTH	2
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	B

TERAND
 INDUSTRIES, INC.
 P.O. Box 667770
 Pompano Beach, FL 33066
 www.terandstore.com



CONTACT CLEANER

80611

- Quick-Drying
- Electrical Grade
- Residue-Free
- Plastic-Safe
- High-Purity

DANGER: EXTREMELY FLAMMABLE.
 HARMFUL OR FATAL IF SWALLOWED.
 CONTENTS UNDER PRESSURE.
 SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 11 OZ. (311 Grams)