

Provides a one-step solution to battery terminal corrosion removal and acid neutralization. Delivers a powerful, heavy duty foam that clings to battery surfaces, provides extended contact time and neutralizes acid quickly. Helps eliminate power leaks and aids in restoring full starting power.

Features a low odor, non-flammable, water soluble formula. Contains a unique color indicator that turns red in the presence of acid, then changes back to yellow when the acid is neutralized.

Leaves behind a residual film that provides short term corrosion resistance.

FOR USE ON: Fleet Cars, Trucks and Buses, Taxi Fleets, Forklifts, Construction, Agricultural and Marine Equipment, Aircraft, Golf Carts, Postal Vehicles, Industrial Battery Backup Systems.

DIRECTIONS:

SHAKE WELL BEFORE USING. Spray on cables, clamps, terminals, brackets, housings and entire battery surface. (Be sure cell covers are tightly sealed). Product will spray out light yellow and turn red in the presence of acid. Allow foam to work for several minutes, then flush off with water. Follow with a second application. If solution still turns red, acid neutralization process is not complete. Allow to set then repeat. For heavy deposits, agitation with a wire brush may be needed. If sprayed foam remains yellow . . . all acid has been neutralized. Allow product to dry and form residual protective film.



CAUTION: Contains Liquefied Petroleum Gas (68476-86-8) and Ethylene Glycol Monobutyl Ether (111-76-2). Do not puncture or incinerate container. Do not expose to heat, sparks or open flame. Do not store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



HAZARD RATING:	HEALTH	1
	FLAMMABILITY	0
	REACTIVITY	0
	PERSONAL PROTECTION	A

TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice

BATTERY TERMINAL CLEANER and PROTECTOR

89018

Extends Battery Life

Provides Residual Corrosion Prevention

Increases Power Output

Includes Color Performance Indicator

CAUTION:
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 18 OZ. (1 LB. 2 OZ.) (510 Grams)