

**CONTAINS NO CHLORINATED SOLVENTS
OR SILICONES**

A clean, clear, long lasting oil which provides a fast, economical solution to many lubricating jobs. Has good penetrating and creeping qualities which helps free many frozen mechanisms. Has little or no effect on plastics, rubber and painted surfaces. Perfect for use on all metal parts, excellent on aluminum.

DIRECTIONS:

Apply generously to sticking surfaces. Reapply as needed.

NOTE: To prevent staining of aluminum from mortar or cement, be sure to spray a heavy coating directly on the aluminum surface just prior to the mortar application.



DANGER: Contains White Mineral Oil (8042-47-5) and Liquefied Petroleum Gas (68476-86-8). Do not use near heat, sparks or open flame. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID: IF EYE

CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN**

CONTACT: Wash with soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION:

When mist has been inhaled, remove victim to fresh air. If breathing is difficult, seek medical attention immediately.

IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

**KEEP OUT OF REACH
OF CHILDREN**



HMIS RATING:	HEALTH	0
	FLAMMABILITY	1
	REACTIVITY	0
	PERSONAL PROTECTION	B

**TERAND
INDUSTRIES, INC.**

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice

**LIGHT OIL
LUBRICANT**

94412

For Awnings, Windows,
Sliding Doors, and Anywhere
Else A Clean Lubricating
Film Is Required

DANGER: EXTREMELY FLAMMABLE.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 12 OZ. (340 Grams)