

Metallic Coatings (MCP) Do Not Exceed 80% VOC or 1.90 MIR.

A high solids zinc rich coating that forms an electrolytic bond on metal surfaces and prevents the formation of rust and corrosion. Prevents further damage and stops creepage in areas where rusting has already occurred. Provides a cold applied coating which equals the performance of hot dip galvanize treatments. Resists abrasion and large temperature fluctuations.

TYPICAL USES: Structural steel and wire, truck and auto bodies, gutters and downspouts, ships, boats, trailers and docks, marine, farm and road equipment, signs and fencing, tanks and piping, ducts and culverts, air conditioning units, ornamental and antique metal, dairy equipment and oil rigs.

DIRECTIONS:

SHAKE CAN VIGOROUSLY BEFORE AND DURING USE. Shake can vigorously until agitator ball begins to rattle. Continue shaking for at least one minute after to ensure that all the zinc is in suspension. Surface must be free from all loose rust, oil, grease and old paint. Spray with a sweeping motion holding can no closer than 10 inches from surface. Coating should be touch dry in 15 minutes. May be painted over after allowing approximately six hours to dry. Cures in 24 to 48 hours. Several thin coats are better than one heavy coat.

IMPORTANT: To prevent clogging: After each use, invert can and spray a few short bursts to clear valve.



DANGER: Contains Liquefied Petroleum Gas (68476-86-8), Toluene (108-88-3), Zinc (7440-66-6), and Petroleum Distillates (64742-47-8). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. **WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects, and other reproductive harm.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



HMIS RATING:	HEALTH	2
	FLAMMABILITY	3
	REACTIVITY	1
	PERSONAL PROTECTION	1

TERAND INDUSTRIES, INC.
 P.O. Box 667770
 Pompano Beach, FL 33066
 www.terandstore.com



GOLD ZINC GALVANIZE

95814

Corrosion Proof Coating

Electrically Bonds To Metal
 Prevents Rust

DANGER: EXTREMELY FLAMMABLE.
 HARMFUL OR FATAL IF SWALLOWED.
 VAPOR HARMFUL.
 CONTENTS UNDER PRESSURE.
 SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 14 OZ. (396 Grams)