

**Multi-Purpose Dry Lube Products Do Not Exceed 50% VOC.
FEATURES AND BENEFITS:**

A fast drying lubricant that forms a thin, black film imparting excellent anti-friction and anti-seizure properties to surfaces. Provides even dispersion of graphite film. Effective over a broad temperature range -100°F to 850°F (-73°C to 454°C). Performs under extreme pressure. Does not contain oil or moisture based diluents. Inert to oils, water and alkalis. Minimizes dust and dirt pick-up.

APPLICATIONS:

Use where a dry lubricant is essential and petroleum products must be avoided. Tracks, bearings, conveyor parts, flat springs, hinges, switches, couplings, die casting machines, oven parts, automotive and industrial gaskets, cables and open gears, thread lubricant (anti-seize), all metal to metal friction, internal combustion engine components (assembly and break-in) and all pre-assembly operations where dust and dirt free lubrication is required.

DIRECTIONS:

1. For best results, use when can is between 70°F and 90°F (21°C and 32°C).
2. Shake at least one minute after rattle is heard and occasionally during use.
3. Point opening of sprayhead toward object, holding can 6" to 8" (15 to 20 cm) from surface.
4. Press sprayhead firmly. Apply a thin coat and allow to dry.
5. If clogging develops, turn sprayhead ¼ turn or remove and clean sprayhead slot. DO NOT stick pin or other object into can opening. Gently replace sprayhead with a twisting motion, holding top of can and sprayhead opening pointed away from you.
6. After spraying, turn can upside down and spray for two seconds to clean sprayhead.
7. Discard empty can in trash pick-up. DO NOT incinerate or compact.



**MADE IN THE
U.S.A.**

DANGER: Contains Acetone (67-64-1), Propane (74-98-6), Isopropyl Alcohol (67-63-0), n-Butane (106-97-8), Toluene (108-88-3), and Graphite (7782-42-5). VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F (49°C).

FIRST AID: IF EYE CONTACT:

Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Vapors may ignite explosively. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stove, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening windows and doors to achieve cross-ventilation.

Use only with adequate ventilation. Do not breathe dust, vapors, or spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA approved) or leave the area. Close container after each use. Avoid contact with eyes, skin, and clothing.

For further
information consult
Material Safety Data Sheet.

**KEEP OUT OF REACH
OF CHILDREN**



HMIS RATINGS	HEALTH	1
	FLAMMABILITY	4
	REACTIVITY	3
	PERSONAL PROTECTION	G

**TERAND
INDUSTRIES, INC.**

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice

DRY GRAPHITE LUBRICANT

96214

High Temperature
Electrically Conductive

Extends Life of Gears,
Chains, Threaded
Connections, Bearings
and more!

DANGER: EXTREMELY FLAMMABLE
LIQUID AND VAPOR. VAPORS MAY CAUSE
FLASH FIRE. CONTENTS UNDER
PRESSURE. SEE OTHER CAUTIONS ON
BACK PANEL.

NET WT. 14 OZ. (396 Grams)