

No Chlorinated Solvents (No 1,1,1-Trichloroethane)

Chemically neutralizes rust and leaves a tough, long term, rust preventative coating. Seals, protects and prolongs the life of ferrous metal. Once dry, the treated area will be darker in color and more uniform in appearance with a durable, protective finish that can be painted if desired.

NOTE: Wearing chemical resistant gloves is recommended.

DIRECTIONS:

1. For best results, workpiece and can should be at room temperature (above 65°F).
2. Surfaces must be clean, dry and free of grease, dirt and oil. Remove loose rust and paint with coarse sandpaper or a wire brush.
3. Before using, shake can until ball rattles freely for at least one minute. Holding the can 8 to 10 inches from the surface, spray a thin, even coating onto the rusted metal. Avoid over application, sagging and dripping. In some cases, a second application may be useful to insure complete coverage and treatment. Wait until the first coat is completely dry before making a second application. A second application may not necessarily cause the surface to darken further. May be painted after final application has cured for approximately 6 hours.



MADE IN THE U.S.A.

DANGER: Contains Ethyl Alcohol (64-17-5), Liquefied Petroleum Gas (68476-85-7), Propylene Glycol Monomethyl Ether (107-98-2), and Tannic Acid (1401-55-4). Use only in a well-ventilated area. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat, sparks or open flame. Do not store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



HAZARD RATING	HEALTH	1
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	B

TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com



RUST EXTERMINATOR

96511

Eliminates Rust

Stops Corrosion

Paintable

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 11 OZ. (311 Grams)