

**EYE PROTECTION REQUIRED
SHAKE WELL BEFORE USE
INCLUDES INTERCHANGEABLE
HORIZONTAL and VERTICAL SPRAY ACTUATORS**

Restores stained and discolored tile to a like-new condition. Eliminates the need for costly ceiling tile replacement. Does not affect acoustical properties. Excellent for both smooth and rough surfaces. Will not cause warp or sag. Coating is nonflammable when dry and does not change the fire rating of the tile to which it has been applied.

SURFACE PREPARATION:

Remove loose dust and dirt by wiping tile gently with a dry rag or duster. Cover surfaces under area to be treated with newspaper or a drop cloth. Protect other areas with masking tape. Tile must be dry. Leaks which have caused water stains must be repaired prior to application.

DIRECTIONS:

SHAKE VIGOROUSLY BEFORE AND DURING USE. Replace button with large vertical action actuator for application on installed tile. When possible, remove tiles to a well ventilated area before application. Shake can vigorously until agitator ball rattles freely. Continue shaking for at least one minute. Shake occasionally during use. Hold can 8 to 10 inches from tiles to be coated. Apply with a sweeping motion using several thin coats. Allow each coat to dry for at least two minutes before applying next coat. If coating runs, can is too close to surface. Feather edges into the remainder of the ceiling by holding can further away during application.

IMPORTANT: After application, clean valve by turning can upside down and applying short burst to clear actuator.



DANGER: Contains Liquefied Petroleum Gas (68476-85-7), Ethyl Alcohol (64-17-5), Hydrous Magnesium Silicate (14807-96-6), Acetone (67-64-1), Titanium Dioxide (13463-67-7) and Toluene (108-88-3). Use of chemical resistant gloves is recommended, especially if skin is subject to allergy or rash. Avoid contact with or inhalation of spray mist. Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. **WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

HMIS RATING:	HEALTH	1
	FLAMMABILITY	3
	REACTIVITY	1
	PERSONAL PROTECTION	1

TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com



The Maintenance Professional's Choice

ACOUSTICAL TILE RESTORER

96715

White Color

Covers Stains And
Discolorations

Will Not Affect Acoustical
Properties

Non-Flammable When Dry

DANGER: EXTREMELY FLAMMABLE.
VAPOR HARMFUL.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 15 OZ. (425 Grams)