

Metallic Coatings Do Not Exceed 65% VOC or 1.40 MIR.

RED INSULATING VARNISH quickly dries to a tough, glossy, flexible coating that protects electrical equipment against moisture and corrosion. The film resists cracking and chipping. Exhibits high arc resistance and has high dielectric strength. Once dry, the surface resists current leakage, insuring optimal efficiency of electrical equipment. Strengthens and repairs worn out and damaged insulation and helps prevent short circuiting and flash-off.

APPLICATIONS: Excellent protective coating for electric equipment including Motor Windings, Commutator Ends, Field Coils, Armatures, Switchboard Parts, Bus Bars, and other exposed Metal Parts. Effective as a finish coat.

DIRECTIONS:

1. Surface must be clean and dry before painting. For best results, use when can is between 70°F and 90°F (21°C and 32°C).
2. Shake can at least one minute before and occasionally during use.
3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25 cm). Several light coats give a better finish than one heavy coat.
4. If clogging develops, turn spray button 1/4 turn or remove and clean button slot. Do not stick objects into can opening.
5. After painting, turn can upside down and spray for 2 seconds to clean spray button.
6. Discard empty can in trash pick up. Do not incinerate or compact.



CONTAINS: Acetone (67-64-1), Propane (74-98-6), Red Iron Oxide (1309-37-1), n-Butane (106-97-8), Toluene (108-88-3), n-Butyl Acetate (123-86-4), Glycol Ether EP (2807-30-9), Isopropyl Alcohol (67-63-0), Xylene (1330-20-7), OTHER

INGREDIENTS: *Contents Partially Unknown* Phenolic-Resin (68122-96-3)

DANGER: VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F (49°C).

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



NOTICE: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain damage and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Vapors may ignite explosively. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors, and other sources or ignition during use and until all vapors are gone. Prevent build-up of vapors by opening windows and doors to achieve cross-ventilation. Use only with adequate ventilation. Do not breathe dust, vapors, or spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA approved) or leave the area. Close container after each use. Avoid contact with eyes, skin, and clothing. **WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

HMS RATING:	HEALTH	1
	FLAMMABILITY	4
	REACTIVITY	3
	PERSONAL PROTECTION	B

TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice

RED INSULATING VARNISH

97816

Quick Dry, Flexible,
Non-Conductive Coating
Insulates and Protects
Electrical Equipment

Resists Chemicals, Oil, and
Moisture

Reduces Current Leakage

High Dielectric Strength

DANGER: EXTREMELY FLAMMABLE
LIQUID AND VAPOR.
VAPORS MAY CAUSE FLASH FIRE.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 16 OZ. (1 LB.) (454 Grams)