

NON-CHLORINATED

Sprays as a deep penetrating liquid that flows into areas which are difficult to lubricate. Then, as the solvent carrier evaporates, the liquid forms into a grease that is resistant to high temperature and pressure.

After setting up, the grease will not wash away with water or steam and will resist throw-off and heavy shock load. Withstands acid, salt spray and oxidation.

USE ON: Wire rope, open gears, linkages, draglines, fittings, winches, cranes, cams, valves, cables, hoists, pulleys and rollers.

DIRECTIONS: First, spray up close to flush off old grease and dirt build-up. Then spray a thin film on surface to be lubricated. Liquid will creep and penetrate then gel in approximately 15 - 20 minutes.



DANGER: Acetone (67-64-1), Naphtha (Petroleum), Hydro-treated Heavy (64742-48-9), Naphtha (Petroleum), Light Aliphatic (64742-89-8), and Carbon Dioxide (124-38-9). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

| | | |
|--------------|---------------------|---|
| HMIS RATING: | HEALTH | 1 |
| | FLAMMABILITY | 3 |
| | REACTIVITY | 0 |
| | PERSONAL PROTECTION | B |

TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice

RED SPRAY GREASE

98011

Lithium-Based

High Temperature and Pressure Resistance

Prevents Water Washout

Withstands Harsh Chemical Environments

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 11 OZ. (311 Grams)