

**Contains NO Chlorinated Solvents
(NO 1,1,1-Trichloroethane) • NO Hexane**

An all weather, multi-purpose, thick, water-resistant grease. Heat stable to 350°F. White color helps indicate lubricated areas and reduces staining.

USE ON: Gears, chains, sprockets, linkages, slides, bearings, cranks, pinions, worms and rollers.

USED BY: Industrial facilities, marine, aircraft and automotive industry, municipalities, farms, homes and offices, any equipment maintenance operation.

DIRECTIONS: SHAKE WELL BEFORE USING. Spray on a clean, dry surface from a distance of 6 to 8 inches. Insert extension tube into actuator orifice for pinpoint application. Tube package included in carton. Repeat application periodically.



DANGER: Acetone (67-64-1), Liquefied Petroleum Gas (68476-86-8), Naphtha (Petroleum), Hydrotreated Heavy (64742-48-9), Naphtha (Petroleum), Light Aliphatic (64742-89-8), Naphtha (Petroleum), Hydrotreated Light (64742-49-0), and Zinc Oxide (1314-13-2). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid breathing of spray mist and continuous breathing of vapor. Avoid contact with eyes or prolonged contact with skin. Do not take internally. May be harmful or fatal if swallowed. Call physician immediately. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

For further information, consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

GHS RATING	HEALTH	1
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	B

TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com



The Maintenance Professional's Choice

WHITE LITHIUM GREASE

99011

Deep Penetrating
Heavy Duty
Non-Staining
Water-Resistant

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE SKIN AND EYE IRRITATION. CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 11 OZ. (311 Grams)