

# MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

## SECTION I - PRODUCT IDENTIFICATION

**Product Name:** De-Icer  
**Product Number:** 515  
**Product Type:** AEROSOL  
**Supplier's Name:** Terand Industries, Inc.  
**Supplier's Address:** P.O. Box 667770, Pompano Beach, FL 33066  
**D.O.T. Hazard Class:** CONSUMER COMMODITY - ORM-D

**Formula:** Proprietary  
**Date Prepared:** 12/27/07  
**Emergency Phone:** (800) 535-5053  
**Information Phone:** (954) 974-5440

**HMIS Rating** (Based on Aerosol Conc.):  
0-Minimal 1- Slight 2- Moderate  
3- Serious 4- Extreme  
**HEALTH:** 1 **FIRE:** 3 **REACTIVITY:** 0  
**Personal Protection :** B

## SECTION II - INGREDIENTS

CHEMICAL NAME	CAS #	%WT	313/Chem	Skin	Carcinogen	PEL	TWA/TLV
Isopropyl Alcohol	67-63-0	80-100	NO	NO	NO	400ppm	400 ppm
Propylene Glycol	57-55-6	05-10	NO	NO	NO	N/E	N/E
Carbon Dioxide Propellant	124-38-9	01-05	NO	NO	NO	10,000ppm	10,000ppm

## SECTION III - PHYSICAL DATA

### Data Below Based On Aerosol Concentrate Only:

Boiling Point: ~140° F

pH: N/A

Solubility In Water: Complete

Appearance / Odor: Clear Colorless Liquid, Mild Alcohol Odor

Vapor Density(Air=1): >1

Specific Gravity (H<sub>2</sub>O=1)@75°F: 0.797

### Data Below Based On Total Contents:

Vapor Pressure of can (psig @70°F): 85

Total VOC %: ~ 97%

## SECTION IV - FIRE AND EXPLOSION DATA

**Flash Point** (of Concentrate Only): 45° F (T.O.C.)

**Flammability** (as per USA Flame Projection Test): Extremely-Flammable Spray

**Extinguishing Media:** Foam, CO<sub>2</sub>, Dry Media

**Special Fire Fighting Procedures:** Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.

**Unusual Fire and Explosion Hazards:** Exposure to temperature above 120° F may cause bursting.

## SECTION V - REACTIVITY DATA

**Stability:** Material Stable.

**Hazardous Polymerization:** Will not Occur.

**Incompatibility:** Avoid contact with strong oxidizing agents, strong acids and strong alkalies.

**Hazardous Decomposition Products:** Carbon Dioxide, Carbon Monoxide.

## SECTION VI - STORAGE AND HANDLING

**KEEP OUT OF REACH OF CHILDREN.**

For Industrial and Institutional use only.

Store in a cool, dry area away from heat or open flame.

Do not store at temperatures above 120° F.

**NFPA Code 30B Rating:** Level 3 Aerosol.

## SECTION VII - HEALTH AND FIRST AID

### PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

**Eyes:** May cause moderate irritation.

**Skin:** Frequent or prolonged contact may cause irritation. May aggravate existing skin conditions.

**Inhalation:** Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects. May aggravate existing respiratory conditions.

**Ingestion:** Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis. May cause mild, reversible liver effects.

### FIRST AID PROCEDURES:

**Eyes:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

**Skin:** Wash with soap and water. If irritation persists seek medical attention.

**Inhalation:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

**Ingestion:** Do not induce vomiting. Seek medical attention immediately.

## SECTION VIII - SPECIAL PROTECTION DATA

**Respiratory Protection:** None needed for proper use in accordance with label directions.

**Ventilation:** Provide local exhaust to keep air concentration of ingredients listed in Section II below established exposure limits.

**Protective Gloves:** Use chemical resistant gloves if hand contact will be made.

**Eye Protection:** Always wear safety glasses or chemical proof goggles when working with any chemical.

## SECTION IX - SPILL OR LEAK PROTECTION

**STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:** Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

**WASTE DISPOSAL METHOD:** Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

**NOTICE:** The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.