

TERAND

The Maintenance Professional's Choice

DRY GRAPHITE LUBRICANT

96214

FOR USE ON:

- Tracks • Bearings • Conveyor Parts • Hinges
- Flat Springs • Oven Parts • Switches
- Couplings • Die Casting Machines
- Automotive and Industrial Gaskets
- Cables and Open Gears
- Thread Lubricant (Anti-Seize)



A fast drying lubricant that forms a thin, black film imparting excellent anti-friction and anti-seizure properties to surfaces. Provides even dispersion of graphite film. Effective over a broad temperature range -100°F to +850°F (-73°C to +454°C). Performs under extreme pressure. Does not contain oil or moisture-based diluents. Inert to oils, water, and alkalis. Minimizes dust and dirt pick up. Used where a dry lubricant is essential and petroleum products must be avoided.

- All Metal-to-Metal Friction
- Internal Combustion Engine Components
- All Pre-assembly Operations where dust and dirt free lubrication is required

- Fast Drying Lubricant
- Provides Even Dispersion of Graphite Film
- Excellent Anti-Friction and Anti-Seizure Properties

- Does Not Exceed 50% VOC
- Extends Life Of Gears Chains, Threaded Connections, And Bearings
- Inert to Oils, Waters and Alkalis



TERAND INDUSTRIES, INC.

P.O. Box 667770 • Pompano Beach, FL 33066-7770

www.terandstore.com

